

CONTENTS

| | |
|--|-------------|
| 1 GROUTING ISSUES RELATED TO THE VERTICAL CLOSED-LOOP GROUND HEAT EXCHANGER | 1-1 |
| Environmental, Geological and Practical Aspects of Grouting | 1-1 |
| <i>Reasons for Grouting a Borehole</i> | <i>1-1</i> |
| <i>Criteria for Obtaining a Proper Grout Seal.....</i> | <i>1-6</i> |
| <i>Practical Considerations for Obtaining a Proper Grout Seal.....</i> | <i>1-7</i> |
| How Much of the Borehole to Grout..... | 1-8 |
| Appropriate Grouting Materials | 1-8 |
| <i>Bentonite-Based Grouts</i> | <i>1-9</i> |
| <i>Cement-Based Grouts</i> | <i>1-11</i> |
| <i>Selection of an Appropriate Grouting Material.....</i> | <i>1-15</i> |
| Evaluation of Common Borehole Sealing Methods..... | 1-16 |
| <i>Shoveling Cuttings from Surface</i> | <i>1-16</i> |
| <i>Leaving Drilling Mud in the Borehole</i> | <i>1-19</i> |
| <i>Borehole Collapse</i> | <i>1-19</i> |
| <i>Pouring Grout Slurry from Surface</i> | <i>1-21</i> |
| <i>Pressure Tremie Grouting</i> | <i>1-23</i> |
| Regulations Pertaining to GHEX Boreholes..... | 1-23 |
| | |
| 2 GROUT PROPERTIES AND VERTICAL GHEX DESIGN..... | 2-1 |
| Engineering Properties of Grouting Products..... | 2-1 |
| <i>Bentonite Grouts.....</i> | <i>2-1</i> |
| <i>Bentonite-Additive Mixtures</i> | <i>2-4</i> |
| <i>Cement Grouts</i> | <i>2-7</i> |
| <i>Cement-Additive Mixtures.....</i> | <i>2-8</i> |
| Borehole Thermal Resistance | 2-9 |
| <i>Grout Shape Factor</i> | <i>2-12</i> |
| <i>Borehole Thermal Resistance</i> | <i>2-14</i> |
| <i>Incremental Grout Resistance - Alternate Method.....</i> | <i>2-18</i> |

| | |
|--|-------------|
| <i>IGSHPA Design Equation</i> | 2-19 |
| Specification of a GHEX Grouting Material | 2-19 |
| <i>Thermal Considerations</i> | 2-19 |
| <i>Pumping and Placement Considerations</i> | 2-20 |
| <i>Environmental Considerations</i> | 2-21 |
| 3 GROUTING VERTICAL BOREHOLES | 3-1 |
| Pre-Grouting Activities | 3-1 |
| <i>Grouting Pump Selection</i> | 3-1 |
| <i>Grout Mixing Equipment Selection</i> | 3-9 |
| <i>Grout Volume Calculations</i> | 3-12 |
| <i>Grouting Cost Estimation</i> | 3-16 |
| Field Grouting Procedures | 3-17 |
| <i>Insertion of the Tremie Pipe</i> | 3-17 |
| <i>Mixing of the Grouting Material</i> | 3-20 |
| <i>Pumping the Grouting Material</i> | 3-21 |
| <i>Removal of the Tremie Pipe</i> | 3-22 |
| <i>Other Grouting Considerations</i> | 3-22 |
| Post-Grouting Activities | 3-23 |
| <i>Equipment Cleanup</i> | 3-23 |
| <i>Site Cleanup</i> | 3-23 |
| <i>Grout Report</i> | 3-23 |
| 4 REFERENCES | 4-1 |
| A BENTONITE GROUTING PRODUCTS | A-1 |
| B BENTONITE GROUT PUMPING CHARACTERISTICS | B-1 |
| C FIELD VERIFICATION OF BOREHOLE RESISTANCE | C-1 |
| Field Test Overview | C-1 |
| Summary of Field Tests | C-1 |
| Results | C-3 |
| D PUMP AND GROUT EQUIPMENT MANUFACTURERS | D-1 |
| AA IGSHPA ADDENDUM | AA-1 |