
Low-Power CMOS Design for Wireless Transceivers



Alireza Zolfaghari

Foreword by Behzad Razavi

Contents

| 1. | INTRODUCTION | | | | | |
|----|--------------|--|-------------|--|--|--|
| | 1.1 | Wireless Networks | | | | |
| | 1.2 | GPS | 2 | | | |
| | 1.3 | Overview of Topics | 3 | | | |
| 2. | TR | ANSCEIVER ARCHITECTURE | 5 | | | |
| | 2.1 | Introduction | | | | |
| | 2.2 | Receiver Architectures | 5 | | | |
| | | 2.2.1 Heterodyne Receivers | 5 7 9 | | | |
| | | 2.2.2 Homodyne Receivers | 7 | | | |
| | | 2.2.3 Image-Reject Receivers | g | | | |
| | 2.3 | | | | | |
| | | 2.3.1 Direct-Conversion Transmitters | 10 | | | |
| | - | 2.3.2 Two-Step Transmitters | 10 | | | |
| | 2.4 | Proposed Transceiver Architecture | 11 | | | |
| | 2.5 | Compatibility with GPS | | | | |
| 3. | STA | ACKED INDUCTORS AND | | | | |
| | TRA | NSFORMERS | 17 | | | |
| | 3.1 | Introduction | 17 | | | |
| | 3.2 | Definitions of the Quality Factor | | | | |
| | 3.3 | Large inductors with high self-resonance frequencies | | | | |
| | 3.4 | Derivation of Self-Resonance Frequency | | | | |
| | 3.5 | Modification of Stacked Inductors | | | | |
| | 3.6 | Stacked Transformers | 28 | | | |
| | 3.7 | Experimental Results | 32 | | | |
| | | | | | | |

| vi | LOW-POWER | CMOS | DESIGN FOR | WIRELESS | TRANSCEIVERS |
|----|-----------|-------------|------------|----------|--------------|
|----|-----------|-------------|------------|----------|--------------|

| 4. | RECEIVER FRONT END | | | | |
|----|--------------------|---|-----------|--|--|
| | 4.1 | Introduction | | | |
| | 4.2 | Low-Noise Amplifier | 41 | | |
| | | RF Mixers | 45 | | |
| | 4.4 | First Downconversion | 46 | | |
| | 4.5 | Second Downconversion | 52 | | |
| | | 4.5.1 Divide-by-Two Circuit | 52 | | |
| | | 4.5.2 Passive Mixers | 53 | | |
| 5. | TR | ANSMITTER | 57 | | |
| | 5.1 | Introduction | 57 | | |
| | 5.2 | First Upconversion | 58 | | |
| | 5.3 | Second Upconversion | 58 | | |
| | 5.4 | Power Amplifier | 61 | | |
| 6. | CH | ANNEL-SELECT FILTER | 67 | | |
| | 6.1 | Introduction | 67 | | |
| | 6.2 | Noninvasive Filtering | 67 | | |
| | | 6.2.1 General Idea | 67 | | |
| | | 6.2.2 Noise Performance | 70 | | |
| | | 6.2.3 Filter Tuning | 72 | | |
| | 6.3 | Filter Design | 74 | | |
| | | 6.3.1 Bluetooth Signal | 74 | | |
| | | 6.3.2 Single-Tone Interferers | 74 | | |
| | | 6.3.4 Intermodulation Specification 6.3.4 Order of Filter | 76 | | |
| | 6.4 | | 76 | | |
| | 0.4 | Filter Realization 6.4.1 Transconductor Stage | 78 | | |
| | - | 6.4.2 Input Transconductor and Parallel Resistor | 78 79 | | |
| | | 6.4.3 Capacitors | 80 | | |
| | | 6.4.4 Channel-Select Filter | 82 | | |
| 7. | EXI | PERIMENTAL RESULTS | 87 | | |
| | 7.1 | Introduction | 87 | | |
| | 7.2 | Test Setup | 87 | | |
| | | 7.2.1 Equipment | 87 | | |
| | | 7.2.2 Test Board | 88 | | |
| | | 7.2.3 Noise Figure Measurements at Low Frequencies | 88 | | |
| | 7.3 | First Prototype: RF Front-End Chip | 90 | | |
| | 7.4 | Second Prototype: Transmitter/Receiver Chip | 93 | | |
| 8. | COI | NCLUSION | 97 | | |
| RI | EFER | ENCES | 101 | | |

Contents vii

Index

105