

High-Fidelity Medical Imaging Displays



Aldo Badano • Michael J. Flynn • Jerzy Kanicki

Contents

| | |
|--|-----------|
| List of Figures | xi |
| List of Tables | xv |
| Preface | xvii |
| Chapter 1 Introduction | 1 |
| 1.1 Medical Imaging Display Markets | 1 |
| 1.2 Units of Measure | 2 |
| Chapter 2 High-Fidelity Display Performance | 5 |
| 2.1 Contrast Sensitivity | 5 |
| 2.2 Luminance Response | 7 |
| 2.3 Luminance Range | 9 |
| 2.4 Adaptation | 9 |
| 2.5 Retinal Anatomy and Visual Acuity | 10 |
| 2.6 Veiling Glare | 13 |
| 2.6.1 Glare in the human eye | 13 |
| 2.6.2 Veiling glare in displays | 14 |
| 2.6.2.1 Sources of glare | 14 |
| 2.6.2.2 Effect of veiling glare | 17 |
| 2.7 Ambient Light Reflections | 18 |
| 2.7.1 Specular reflection | 19 |
| 2.7.2 Diffuse reflection | 21 |
| 2.8 High-Fidelity Display Requirements | 22 |
| Chapter 3 Cathode-Ray Tubes | 25 |
| 3.1 Cathodes | 26 |
| 3.2 Electron Optics | 28 |
| 3.3 Emissive Structure | 28 |
| 3.4 Signal Electronics | 29 |
| 3.5 Color CRTs | 32 |
| 3.6 Spot Size | 33 |
| 3.7 Monochrome Phosphors | 34 |
| 3.8 Antireflection Surface Treatments | 35 |
| 3.9 Face-plate Absorption | 36 |
| 3.10 Gray-scale Controllers | 36 |

| | | |
|------------------|--|-----------|
| Chapter 4 | Active-Matrix Liquid Crystal Displays | 39 |
| 4.1 | The Liquid Crystal Cell | 40 |
| 4.2 | Efficiency of Light Transmission | 42 |
| 4.3 | Addressing Methods | 43 |
| 4.4 | Elements of an AMLCD | 44 |
| 4.5 | Crosstalk in AMLCDs | 47 |
| 4.6 | Luminance Variations with Viewing Angle | 48 |
| 4.7 | Solutions to Viewing Angle Problem | 51 |
| 4.7.1 | Compensation foils | 51 |
| 4.7.2 | Multiple domain cells | 52 |
| 4.7.3 | Symmetry micro-cells | 53 |
| 4.7.4 | In-plane switching | 53 |
| 4.7.5 | Vertical alignment | 54 |
| | | |
| Chapter 5 | Active-Matrix Organic Light-Emitting Displays | 55 |
| 5.1 | Introduction to OLEDs | 55 |
| 5.1.1 | History of OLEDs | 56 |
| 5.1.2 | OLEDs for displays | 57 |
| 5.1.3 | OLED structures | 58 |
| 5.1.4 | EL organic materials | 62 |
| 5.2 | Evaluation of Device Opto-Electronic Performance | 65 |
| 5.3 | Device Configuration and Display Fabrication | 65 |
| 5.3.1 | Conventional OLED | 66 |
| 5.3.2 | Side-by-side subpixels | 67 |
| 5.3.3 | White OLED filtering | 67 |
| 5.3.4 | Blue OLED down-conversion | 69 |
| 5.3.5 | Microcavity OLEDs | 69 |
| 5.3.6 | Color-tunable OLEDs | 70 |
| 5.3.7 | Pyramid-shaped pixel OLEDs | 70 |
| 5.3.8 | Stacked OLEDs | 71 |
| 5.4 | OLED Stability and Encapsulation for Displays | 74 |
| 5.4.1 | Impact of moisture and oxygen | 74 |
| 5.4.2 | Influence of dark spots | 77 |
| 5.4.3 | Encapsulation methods | 79 |
| 5.5 | Display Addressing and Driving Circuit | 81 |
| 5.5.1 | PM-addressing method | 82 |
| 5.5.2 | AM-addressing method | 84 |
| 5.6 | TFT Technology for AM Displays | 85 |
| 5.6.1 | a-Si:H TFT technology | 86 |
| 5.6.2 | Poly-Si TFT Technology | 87 |
| 5.6.3 | Pixel electrode circuits | 88 |
| 5.7 | Methods to Improve AMOLED Contrast Ratio | 100 |

| | | |
|------------------|--|------------|
| 5.8 | Current Market and Future Trends | 101 |
| 5.8.1 | Comparison between OLED and non-LED displays | 101 |
| 5.8.2 | Comparison between OLEDs and inorganic LEDs | 103 |
| 5.8.3 | Current and future challenges | 103 |
| Chapter 6 | Display Image Quality Metrics | 105 |
| 6.1 | Luminance Response | 105 |
| 6.1.1 | Luminance calibration | 107 |
| 6.1.2 | Angular emission | 109 |
| 6.2 | Contrast Ratio | 114 |
| 6.2.1 | Veiling glare | 114 |
| 6.2.2 | Electronic crosstalk | 116 |
| 6.3 | Spatial Frequency | 123 |
| 6.4 | Noise | 125 |
| 6.5 | Reflectance | 129 |
| 6.5.1 | Reflectance models | 130 |
| 6.5.2 | Measuring display reflections | 131 |
| 6.5.3 | Bidirectional reflection distribution function | 135 |
| 6.6 | Evaluation Software and Standards | 136 |
| | References | 139 |
| | Index | 151 |